



XVR VSLR616-PT

System		
Main Processor	Embedded processor	
Operating System	Embedded LINUX	
Video		
Input	16 channel, BNC	
Standard	Analog	NTSC/PAL
	HDCVI	1080P/720P HDCVI Camera
	IP	16+2 up to 5Mp
Audio		
Input	1 channel, RCA	
Output	1 channel, RCA	
Two-way Talk	Reuse audio input/output channel 1	
Display		
Interface	1 HDMI, 1 VGA	
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768	
Display Split	1/4/8/9/16	
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Video/Audio Compression	H.264/G.711	
Resolution	1080N(960*1080)/720P(1280*720)/960H(960*576/960480)/ D1(704*576/704*480)/HD1(352*576/352*480) /BCIF(704*288/704*240) CIF(352*288/352*240) / QCIF(176*144/176*120)	
Record Rate	Main Stream:	1*1080N/720P(1~25/30fps)+15*(1~12/15fps) /960H/D1/HD1/BCIF/ CIF/QCIF (1~25/30fps)
	Extra Stream	CIF/QCIF(1~7fps)
Bit Rate	1~4096Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous),MD), Stop	
Record Interval	1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection		
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank	
Playback & Backup		
Sync Playback	1/4/9/16	
Search Mode	Time/Date, MD & Exact search (accurate to second)	
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode	USB Device/Internal SATA burner/Network	
Network		
Ethernet	RJ-45 port (10/100M)	
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P	
Max. User Access	128 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Storage		
Internal HDD	1 SATA port, up to 6TB	
Auxiliary Interface		
USB Interface	2 ports(1 Rear), USB2.0	
RS485	1 port, For PTZ Control	
General		
Power Supply	DC12V/2A	
Power Consumption	10W(without HDD)	
Working Environment	-10°C ~+55°C / 10%~90%RH / 86~106kpa	
Dimension(WxDxH)	Compact 1U, 260mmx220mmx40mm	
Weight	0.75KG(without HDD)	